



ELECTRO ADAPTER INC.
CHATSWORTH, CALIFORNIA, USA 91311
PHONE (818) 998-1198
FAX (818) 709-5773

SECTION 2 - BANDING TERMINATION
SHRINK BOOT, EMI/RFI,
SHIELD SOCK, LOW PROFILE
SAE AS85049 CATEGORY 1





E * * 32

SHEET 1 OF 2


Table 2 - Cable Entry Data

ENTRY ORDER NUMBER	Z ±.031 DIA.
03	.188
04	.250
05	.312
06	.375
07	.438
08	.500
09	.562
10	.625
11	.688
12	.750
13	.812
14	.875
15	.938
16	1.000
18	1.125

WHEN MAXIMUM CABLE ENTRY EXCEEDS THE CONNECTOR INTERFACE DIAMETER, A 2 PIECE ADAPTER WILL BE SUPPLIED. CONSULT FACTORY FOR LARGER ENTRY SIZES.



CONFIG FOR 2 PIECE



ASSEMBLY PART NUMBER

TO ESTABLISH YOU P/N, USE THE FOLLOWING EXAMPLE

E 41 32 R 23 08 1 06 S 51

FUNCTION DESIGNATOR
A-NON EMI ADAPTER

CONNECTOR CODE NUMBER - TABLE 1 ⑥

SERIES PART NUMBER

ADAPTER STYLE
R = 90° ADAPTER
A = 45° ADAPTER
J = 90° ADAPTER (DIE-CAST)
K = 45° ADAPTER (DIE-CAST)

ACCESSORY ORDER NUMBER-TABLE 1

CABLE ENTRY ORDER NUMBER-TABLE 2

MOD CODE ⑥

PLATING CODE NUMBER-TABLE 4 ⑥

GLAND & O'RING MATERIAL OPTION
B - NEOPRENE & BUNA-N
S - SILICONE
N - NONE (NON ENVIROMENTAL)

SHIELD LENGTH CODE
SHIELD LENGTHS ARE CHOSEN IN 1.00 INCH INCREMENTS (I.E. 08 = 8.00"). MINIMUM ORDER LENGTH IS 3.00" CODE 03 (00 FOR NO SHIELD). MAXIMUM ORDER LENGTH IS 200.00" CODE 200.

SHIELD OPTION
1 - SINGLE LAYER TINNED COPPER
2 - DOUBLE LAYER TINNED COPPER
3 - SINGLE LAYER SILVER COATED COPPER
4 - DOUBLE LAYER SILVER COATED COPPER
5 - ASSY. SUPPLIED WITH DRIVER BAND LESS SHIELD
0 - NO SHIELDING OR DRIVE BAND REQUIRED.

Table 1 - Order Number Data

E * * 32

SHEET 2 OF 2

Accessory Order Number By Connector Code & Shell Size

ORDER NUMBER	18 (4)	21	32 (2)	40 (3)	41	54	64	61	76	A UNIFIED THREAD	B MAX DIA.	C MAX DIA.	D (7) MAX DIM.	E MAX DIM.	F (7) ±.125 DIM.	G MAX DIM.	H MAX DIM.	K MAX DIM.	M MAX DIM.	N MAX DIM.	ORDER NUMBER
01	8S (B)									.375-32	.750	.531	1.031		.500						01
03	8S (A)									.438-27	.812	.594	1.094		.500						03
04	8S (C)	8			8, 9				8	.438-28	.812	.594	1.000	1.188	.750		.457	1.710	.500	1.730	04
05						8 & 8S				.500-20	.875	.656	.938		.719	1.062	.457	1.710	.500	1.730	05
06	10S (-)							8, A		.500-28	.875	.656	1.562		1.062						06
07				9, A						M12 x 1.0	.719	.656	.938	1.250	.500		.457	1.710	.500	1.730	07
08	10SL (C)	10			10, 11		3		10	.562-24	.844	.719	1.375		.750		.520	1.770	.595	1.850	08
10	10SL(A,B), 12, 12S(B,C)					10, 10S, 10SL		12		.625-24	1.000	.781	1.562		1.062		.520	1.770	.595	1.850	10
11										.625-28	1.000	.781	1.688	1.312	1.062	1.094					11
12				11, B				10, B		M15 x 1.0	.844	.781	1.125		.500		.520	1.770	.595	1.850	12
13	12 & 12S (A)	12		12, 13					12	.688-24	1.062	.844	1.500		.750		.582	1.830	.610	1.870	13
15	14 & 14S (-)		12			12 & 12S	7	14		.750-20	1.125	.906	1.812		.875		.582	1.830	.610	1.870	15
16				13, C						M18 x 1.0	.969	.906	1.188	1.375	.562	1.125	.562	1.830	.610	1.870	16
18		14		14, 15					14	.812-20	1.188	.969	1.500		.812		.645	1.920	.700	1.940	18
19	16 & 16S (-)		14			14 & 14S	12	16		.875-20	1.250	1.031	1.875		.750		.645	1.920	.700	1.940	19
20										.875-28	1.250	1.031	1.938	1.438	1.125						20
21				15, D				14, D		M22 x 1.0	1.094	1.031	1.312		.562		.645	1.920	.700	1.940	21
23		16		16, 17					16	.938-20	1.312	1.094	1.625		.875		.738	2.030	.885	2.030	23
24	18 (-)		16			16 & 16S	19	18		1.000-20	1.375	1.156	2.000	1.500	.719		.738	2.030	.885	2.030	24
25										1.000-28	1.375	1.156	2.062		1.156						25
26				17, E				16, E		M25 x 1.0	1.219	1.156	1.438		.594	1.188	.738	2.030	.885	2.030	26
28		18		18, 19	18	27		18		1.062-18	1.438	1.219	1.688		.875		.926	2.220	.975	2.200	28
29	20 (-)		18							1.125-18	1.500	1.281	2.156		.938						29
30	20 (R)							20		1.125-24	1.500	1.281	1.938	1.562	.625						30
31									18, F	1.125-28	1.500	1.281	2.125		1.188						31
32				19, F						M28 x 1.0	1.344	1.281	1.500		.625		.926	2.220	.975	2.200	32
34										1.188-18	1.562	1.344	1.812		.875		.926	2.220	.975	2.200	34
35	22 (-)	20		20, 21	20	37		20		.938	1.250	1.406	2.250	1.625	1.250	1.219					35
36			20				22		20, G	1.250-28	1.625	1.406	2.250		.688		.926	2.220	.975	2.200	36
37				21, G						M31 x 1.0	1.469	1.406	1.625		.938		1.020	2.370	1.125	2.310	37
39		22		22, 23	22			22		1.312-18	1.688	1.469	1.938		.938						39
40	24 (-)		22				24			1.375-18	1.750	1.531	2.375		1.000						40
41									22, H	1.375-28	1.750	1.531	2.375		1.250						41
42				23, H						M34 x 1.0	1.594	1.531	1.750		.656	1.250	1.020	2.370	1.125	2.310	42
44		24		24, 25	24			24		1.438-18	1.812	1.594	2.000		1.000	1.688	1.020	2.370	1.125	2.310	44
45						61				1.500-18	1.875	1.656	1.875		.938						45
46								24, J		1.500-28	1.875	1.656	2.500		1.250						46
47				25, J						M37 x 1.0	1.719	1.656	1.875		.688	1.250	1.020	2.370	1.125	2.310	47
48										1.562-18	1.938	1.719	2.125		1.062						48
49	28 (-)	24					28			1.625-18	2.000	1.781	2.500	1.812	1.250	1.312					49
51										1.750-18	2.125	1.906	2.062		.938						51
52	32 (B,C)		28			28		32		1.875-16	2.250	2.031	2.750	1.938	1.125	1.344					52
53	32 (A,R)									1.906-18	2.281	2.062	2.438		.750						53
54						32				2.000-18	2.375	2.156	2.312		.969						54
55	36 (B)		32					36		2.062-16	2.469	2.219	3.000		.969						55
56	36 (R)									2.062-24	2.469	2.219	1.875	2.062	.812	1.406					56
57	36 (C)									2.125-16	2.500	2.281	1.875		.812						57
58	36 (A)									2.125-18	2.500	2.281	1.875		.812						58
59					36					2.250-16	2.625	2.406	2.438		1.031						59
60	40 (B)		36					40		2.312-16	2.719	2.469	3.250	2.188	1.000	1.438					60
61	40 (A,C)									2.375-16	2.750	2.531	2.000		.875						61
62										2.500-16	2.875	2.656	2.688	2.750	1.125	1.500					62

NOTES: UNLESS OTHERWISE SPECIFIED.

1 THREADS ARE RIGHT HAND IN ACCORDANCE WITH FED-STD-H28, CLASS 2B.

(2) THREADS NOTED ARE LEFT HAND, CLASS 2B.

(3) THREADS NOTED ARE ISO METRIC, CLASS 6H.

(4) CODE 18 SHELL SIZES ARE FOLLOWED IN PARENTHESIS BY CONNECTOR MFR CODE. SEE CONNECTOR CODE 18 CHART AT RIGHT & EXAMPLE PART NUMBER FOR DETAILS.

5 TABLE 1 LISTS THE MOST USED CONNECTOR CODES. SEE SECTION 11 FOR OTHER CODES AVAILABLE AND COMPLETE CONNECTOR PART NUMBER CROSS REFERENCE.

(6) SEE SUPPORT DATA SECTION FOR PLATING AND MODIFICATION CODE OPTIONS.

(7) ADD .25 TO "D" & "F" FOR CONNECTOR CODES 30, 32 & 61.

(8) SEE SUPPORT DATA SECTION FOR TABLE V & AVAILABLE STYLES

(4) Connector Code 18 Chart

CONNECTOR	CONNECTOR MANUFACTURER
CODE	(MS3100, MS3101, MS3106 & MS3107)
A	AMPHENOL, CLASS A
B	BENDIX, CLASS A, E & R
C	CANNON, CLASS A, E & R
D	MFR. UNKNOWN, CLASS A, E & R
R	AMPHENOL, CLASS R
-	MFR. CODE NOT REQUIRED